



Klemsan®

310129 CTP 2,5

6 mm², Push-in connection, 1 In 1 Out feed-through terminal block,
Insulation material PA, Grey

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V0
	Packing Unit	50
	Weight (g)	—
Dimensions	Width	5,2 mm
	Length	51,60 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	37,30 mm
TSE / CE Technical Data	Nominal Voltage	500 V ~
	Nominal Current	24 A
	Cross Section	2,5 mm ²
	Norm	IEC 61984 / IEC 60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
Connection Data	Minimum solid strand cross section	0,08 mm ²

Maximum solid Strand cross section	4 mm ²
Minimum fine Strand cross section	0,14 mm ²
Maximum fine strand cross section	2,5 mm ²
AWG Conductor Range	28-12
Connection Type	Spring - Cross connection
Insulation Stripping length	8-10 mm
Tightening torque	— Nm

Avrupa standartlarına uygunluk belgesi - CE Certificate

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

**Order
Info**

■	310129	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Grey
■	310121	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Blue
■	310122	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Green
■	310123	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Green
■	310124	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Red
■	310125	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Black
□	310126	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, White
■	310127	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Orange
■	310120	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Beige
■	310128	6 mm ² , Push-in connection, 1 In 1 Out feed-through terminal block, Insulation material PA, Brown