



Klemsan®

310549 SG-PT 2,5GCS 1M

2,5mm², 1 Pole Pin Type Plug Middle Cross-Connectable,
Insulation Material PA, Grey

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V0
Dimensions	Width	5,2 mm
	Length	20,80 mm
	Height	41,90 mm
TSE / CE Technical Data	Nominal Voltage	500 V ~
	Nominal Current	24 A
	Cross Section	2,5 mm ²
	Norm	IEC 61984 / IEC 60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
Connection Data	Minimum solid strand cross section	0,08 mm ²
	Maximum solid Strand cross section	4 mm ²
	Minimum fine Strand cross section	0,14 mm ²
	Maximum fine strand cross section	2,5 mm ²

AWG Conductor Range	28-12
Connection Type	Spring connection
Insulation Stripping length	8-10 mm
Tightening torque	— Nm

Avrupa standartlarına uygunluk belgesi - CE Certificate

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

Order Info

■ 310549 2,5mm², 1 Pole Pin Type Plug Middle Cross-Connectable, Insulation Material PA, Grey

© 2022 Klemsan A.Ş.
www.klemsan.com