



Klemsan®

334120 AVK 2,5/4T

2,5-4mm², screw type, single deck earth terminal block for AVK series, Insulating material PA, Yellow-Green

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	—
	Weight (g)	—
	Continuous Operating Temp.	(min.-max.)
	DIN-EN 45545Z	
Dimensions	Width	6 mm
	Length	42.00 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.50 mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	Nom	EN 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	VDE Norm	EN 60947-7-1/EN 60947-7-2
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²

Minimum fine Strand cross section	0.5 mm ²
Maximum fine strand cross section	6 mm ²
AWG Conductor Range	20-10
Connection Type	screw/vidalı
Insulation Stripping length	10 mm
Tightening torque	0.5/0.8 Nm



Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate

EAC - Russian EAC

RINA Sertifikası - RINA Certificate

Order Info

334120 2,5-4mm²,screw type,single deck earth terminal block for AVK series,Insulation material PA,Yellow-Green